

Austape®

Crepe Paper Tapes

8120XX

TYPICAL APPLICATIONS

- Designed for high performance applications such as masking, bundling, and labeling.
- Metal preparation, painting and coating
- Removes cleanly with no adhesive residue in application temperatures to 93 °C

FEATURES & BENEFITS

- Engineered for holding power
- No adhesive residue
- Excellent adhesion to metal, rubber and plastic
- Conformability for rounding curves and contours
- Clean flat edges for sharp paint lines
- Solvent and moisture resistant to minimise bleedthrough



CONSTRUCTION

Backing: Smooth crepe paper

Adhesive: High performance rubber

COLOUR/S

- Brown

LONG DESCRIPTION

- 70/110 Crepe Paper

Contact your Insulect sales representative or distributor for information on nonstandard sizes

SPECIFICATIONS

- ASTM D6123/D6123M-97

“Austape” is a registered trademark of Insulect Australia Pty Ltd

Product	8120XX	
Tensile Strength	35 N/10mm	20 lbs/in width
Adhesion (to Stainless Steel)	3.28 N/10mm	30 oz/in width
Elongation	10 %	
Total Tape Thickness	0.15 mm	6.0 mils
Maximum Operating Temperature	93 °C	200 °F

Product StockCode	Description	
812015	W=15mm	OD=150mm
812020	W=20mm	OD=145mm
812025	W=25mm	OD=150mm
812030	W=30mm	OD=150mm
812032	W=32mm	OD=140mm
812038	W=38mm	OD=150mm
812040	W=40mm	OD=155mm
812050	W=50mm	OD=150mm
812075	W=75mm	OD=150mm

STORAGE & USAGE CONDITIONS

This tape should be stored in a cool, dry area away from direct sunlight and should be applied to surfaces which are clean, dry and free from grease, oil or other contaminants.

TECHNICAL INFORMATION

The physical and performance characteristics shown in this document are based on testing done by or on behalf of the manufacturer and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user is responsible for determining whether the product is fit for a particular