

Shurtape® (Permacel) Gaffer Vinyl-Coated Cloth Tape

P-665

TYPICAL APPLICATIONS

- Designed as a specialty gaffer grade tape for the arts and entertainment industry
- Perfect for holding wiring, lighting and props without leaving any residue
- Also well suited to seaming, bundling, marking, colour coding and protection

FEATURES & BENEFITS

- High adhesion and tack
- Heat resistant for clean removal
- Hand tearable - no need for knife, scissors or dispenser
- Highly conformable to irregular surfaces and shapes
- Cloth back provides high tensile strength
- Vinyl coating is scuff resistant and protects against dirt, dust and moisture
- Able to be written on with commonly-used markers and ballpoint pens



CONSTRUCTION

Backing: Vinyl coated cloth

Adhesive: Synthetic rubber

STANDARD WIDTH/S

- 24 mm
- 48 mm
- 72 mm

Contact your Insulect sales representative or distributor for information on non-standard sizes

STANDARD LENGTH/S

- 35 m
- 55 m

COLOUR/S

- Black
- Grey
- White

“Shurtape” is a registered trademark of Shurtape Technologies, LLC.

STORAGE & USAGE CONDITIONS

This tape should be stored in a cool, dry area away from direct sunlight and should be applied to surfaces which are clean, dry and free from grease, oil or other contaminants.

TECHNICAL INFORMATION

The physical and performance characteristics shown in this document are based on testing done by or on behalf of the manufacturer and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application before use.

TYPICAL PHYSICAL PROPERTIES

Product	P-665	
Tensile Strength	84.1 N/10mm	48 lbs/in width
Adhesion (to Stainless Steel)	8.76 N/10mm	80 oz/in width
Total Tape Thickness	0.29 mm	11.5 mils
Operating Temperature Range	7 to 93 °C	45 to 200 °F