

Shurtape® (Permacel)

Photographic Masking Tape

P743 CP743

TYPICAL APPLICATIONS

- Engineered specifically for professional photographic reproduction work including cropping and edging negatives for contact printing
- A versatile, reliable tape for use in photo studios, film processing labs, home dark rooms and as a chart tape
- Sealing camera bellow, film holders against light leaks

FEATURES & BENEFITS

- Opaque black matte backing ensures light-free masking for high quality photo reproduction
- Easy to unwind
- Hand tearable
- High quick-stick and adhesion
- Highly conformable



CONSTRUCTION

Backing: Impregnated paper

Adhesive: Synthetic rubber

STANDARD WIDTH/S

- 6 mm
- 12 mm
- 24 mm
- 48 mm

Contact your Insulect sales representative or distributor for information on non-standard sizes

STANDARD LENGTH/S

- 50 m

COLOUR/S

- Black matte

SPECIFICATIONS

- ASTM D6123/D6123M-97

“Shurtape” is a registered trademark of Shurtape Technologies, LLC.

STORAGE & USAGE CONDITIONS

This tape should be stored in a cool, dry area away from direct sunlight and should be applied to surfaces which are clean, dry and free from grease, oil or other contaminants.

TECHNICAL INFORMATION

The physical and performance characteristics shown in this document are based on testing done by or on behalf of the manufacturer and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application before use.

TYPICAL PHYSICAL PROPERTIES

Product	P743 CP743	
Tensile Strength	36.8 N/10mm	21 lbs/in width
Adhesion (to Stainless Steel)	5.47 N/10mm	50 oz/in width
Elongation	7 %	
Total Tape Thickness	0.15 mm	6.1 mils
Operating Temperature Range	7 to 38 °C	45 to 100 °F